

QUICK SEARCH GUIDE

Turbo
Inverter R32

EU Model (Hisense)		Model		Nominal Capacity				Energy Efficiency/Cooling				Energy Efficiency/Heating Average				Energy Efficiency/Heating Warmer				Sound Power		Pipe Size
Indoor Unit	Outdoor Unit	Indoor Unit	Outdoor Unit	Cooling(W)	EER(W/W)	Heating(W)	COP(W/W)	Pdc(W)	SEER	Energy Level	η s.c	Pdh(W)	SCOP	Level	η s.h	Pdh (W)	SCOP	Level	η s.h	IDU(dB)	ODU(dB)	Gas/Liquid(mm)
ACT26UR4RCC8	AUW26U4RS8	ACT-09UR4RCC8	AUW-09U4RS8	2600	4.19	3200	4.27	2600	7.20	A++	340%	3000	4.60	A++	216%	3000	5.35	A+++	252%	54	62	Φ 6.35/Φ 9.52(1/4"/3/8")
ACT35UR4RCC8	AUW35U4RS8	ACT-12UR4RCC8	AUW-12U4RS8	3500	4.00	4000	4.00	3500	7.00	A++	330%	3000	4.60	A++	216%	3000	5.35	A+++	252%	54	62	Φ 6.35/Φ 9.52(1/4"/3/8")
ACT40UR4RCC8	AUW40U4RJ8	ACT-14UR4RCC8	AUW-14U4RJ8	4100	4.00	4600	4.00	4100	6.70	A++	316%	4000	4.40	A+	207%	4000	5.35	A+++	252%	57	64	Φ 6.35/Φ 12.7(1/4"/1/2")
ACT52UR4RCC8	AUW52U4RJ8	ACT-18UR4RCC8	AUW-18U4RJ8	5000	3.67	5500	3.71	5000	6.70	A++	316%	4000	4.40	A+	207%	4000	5.35	A+++	252%	57	64	Φ 6.35/Φ 12.7(1/4"/1/2")
ACT40UR4RJC8	AUW40U4RJ8	AUC-14UR4RJC8	AUW-14U4RJ8	4100	4.40	4600	4.50	4100	7.30	A++	345%	4000	4.60	A++	216%	4000	5.35	A+++	252%	52	64	Φ 6.35/Φ 12.7(1/4"/1/2")
ACT52UR4RJC8	AUW52U4RJ8	AUC-18UR4RJC8	AUW-18U4RJ8	5000	4.00	5500	4.30	5000	7.20	A++	340%	4000	4.60	A++	216%	4000	5.35	A+++	252%	52	64	Φ 6.35/Φ 12.7(1/4"/1/2")
ACT60UR4RJC8	AUW60U4RK8	ACT-21UR4RJC8	AUW-21U4RK8	6200	3.90	7300	4.00	6200	7.50	A++	354%	5500	4.60	A++	216%	5500	5.35	A+++	252%	54	68	Φ 9.52/Φ 15.88(3/8"/5/8")
ACT71UR4RJC8	AUW71U4RK8	ACT-24UR4RJC8	AUW-24U4RK8	7000	3.70	8000	3.80	7000	7.10	A++	335%	5500	4.60	A++	216%	5500	5.35	A+++	252%	54	68	Φ 9.52/Φ 15.88(3/8"/5/8")
AUC105UR4RKC8	AUW105U4RW8	AUC-36UR4RKC8	AUW-36U4RW8	10000	3.85	11000	3.90	10000	7.50	A++	354%	8000	4.60	A++	216%	8000	5.40	A+++	254%	62	69	Φ 9.52/Φ 15.88(3/8"/5/8")
AUC105UR4RKC8	AUW105U6RW8	AUC-36UR4RKC8	AUW-36U6RW8	10000	3.85	11000	3.90	10000	7.50	A++	354%	8000	4.60	A++	216%	8000	5.40	A+++	254%	62	69	Φ 9.52/Φ 15.88(3/8"/5/8")
AUC125UR4RKC8	AUW125U4RW8	AUC-42UR4RKC8	AUW-42U4RW8	12100	3.61	13500	3.75	12100	7.00	-	277%	9000	4.50	-	177%	9000	5.40	-	213%	64	73	Φ 9.52/Φ 15.88(3/8"/5/8")
AUC125UR4RKC8	AUW125U6RN8	AUC-42UR4RKC8	AUW-42U6RN8	12100	3.61	13500	3.75	12100	7.00	-	277%	9000	4.50	-	177%	9000	5.40	-	213%	64	73	Φ 9.52/Φ 15.88(3/8"/5/8")
AUC140UR4RKC8	AUW140U4RW8	AUC-48UR4RKC8	AUW-48U4RW8	13500	3.21	16000	3.41	13500	6.70	-	265%	9000	4.50	-	177%	9000	5.40	-	213%	64	74	Φ 9.52/Φ 15.88(3/8"/5/8")
AUC140UR4RKC8	AUW140U6RN8	AUC-48UR4RKC8	AUW-48U6RN8	13500	3.21	16000	3.41	13500	6.70	-	265%	9000	4.50	-	177%	9000	5.40	-	213%	64	74	Φ 9.52/Φ 15.88(3/8"/5/8")
AUC175UR4RKC8	AUW175U6RW8	AUC-60UR4RKC8	AUW-60U6RW8	16000	2.91	17500	2.97	16000	6.10	-	241%	10000	4.00	-	157%	10000	4.90	-	193%	66	75	Φ 9.52/Φ 15.88(3/8"/5/8")